

GFD-R-P.225
OCCI-WG

Ralf Nyrén, Independent
Florian Feldhaus, Independent
Boris Parák, CESNET
Zdeněk Šustr, CESNET
February 25, 2011
Updated: September 19, 2016

Open Cloud Computing Interface – JSON Rendering

Status of this Document

This document provides information to the community regarding the specification of the Open Cloud Computing Interface. Distribution is unlimited.

Copyright Notice

Copyright ©Open Grid Forum (2012-2016). All Rights Reserved.

Trademarks

OCCI is a trademark of the Open Grid Forum.

Abstract

This document, part of a document series produced by the OCCI working group within the Open Grid Forum (OGF), provides a high-level definition of a Protocol and API. The document is based upon previously gathered requirements and focuses on the scope of important capabilities required to support modern service offerings.

Contents

1	Introduction	3
2	Notational Conventions	3
3	OCCI JSON Rendering	4
3.1	Entity Instance Rendering	4
3.1.1	Resource Instance Rendering	4
3.1.2	Link Instance Rendering	5
3.2	Category Instance Rendering	5
3.2.1	Kind Instance Rendering	6
3.2.2	Mixin Instance Rendering	6
3.2.3	Action Instance Rendering	7
3.3	Entity Collection Rendering	7
3.3.1	Resource Collection Rendering	7
3.3.2	Link Collection Rendering	7
3.4	Category Collection Rendering	7
3.4.1	Kind Collection Rendering	8
3.4.2	Mixin Collection Rendering	8
3.4.3	Action Collection Rendering	8
3.5	Attributes Rendering	8
3.5.1	Attribute Description Rendering	8
4	Security Considerations	9
5	Glossary	10
6	Contributors	10
7	Intellectual Property Statement	11
8	Disclaimer	11
9	Full Copyright Notice	11
A	JSON Rendering Examples	13
A.1	Resource Instance Example	13
A.2	Action Invocation Example	13
A.3	Link Instance Example	14
A.4	Kind Instance Example	14
A.5	Mixin Instance Example	15
A.6	Action Instance Example	15
B	OCCI JSON Schema	15

1 Introduction

The Open Cloud Computing Interface (OCCI) is a RESTful Protocol and API for all kinds of management tasks. OCCI was originally initiated to create a remote management API for IaaS¹ model-based services, allowing for the development of interoperable tools for common tasks including deployment, autonomic scaling and monitoring. It has since evolved into a flexible API with a strong focus on interoperability while still offering a high degree of extensibility. The current release of the Open Cloud Computing Interface is suitable to serve many other models in addition to IaaS, including PaaS and SaaS.

In order to be modular and extensible the current OCCI specification is released as a suite of complementary documents, which together form the complete specification. The documents are divided into four categories consisting of the OCCI Core, the OCCI Protocols, the OCCI Renderings and the OCCI Extensions.

- The OCCI Core specification consists of a single document defining the OCCI Core Model. OCCI interaction occurs through *renderings* (including associated behaviors) and is expandable through *extensions*.
- The OCCI Protocol specifications consist of multiple documents, each describing how the model can be interacted with over a particular protocol (e.g. HTTP, AMQP, etc.). Multiple protocols can interact with the same instance of the OCCI Core Model.
- The OCCI Rendering specifications consist of multiple documents, each describing a particular rendering of the OCCI Core Model. Multiple renderings can interact with the same instance of the OCCI Core Model and will automatically support any additions to the model which follow the extension rules defined in OCCI Core.
- The OCCI Extension specifications consist of multiple documents, each describing a particular extension of the OCCI Core Model. The extension documents describe additions to the OCCI Core Model defined within the OCCI specification suite.

The current specification consists of seven documents. This specification describes version 1.2 of OCCI and is backward compatible with 1.1. Future releases of OCCI may include additional protocol, rendering and extension specifications. The specifications to be implemented (MUST, SHOULD, MAY) are detailed in the table below.

Table 1. What OCCI specifications must be implemented for the specific version.

Document	OCCI 1.1	OCCI 1.2
Core Model	MUST	MUST
Infrastructure Model	SHOULD	SHOULD
Platform Model	MAY	MAY
SLA Model	MAY	MAY
HTTP Protocol	MUST	MUST
Text Rendering	MUST	MUST
JSON Rendering	MAY	MUST

2 Notational Conventions

All these parts and the information within are mandatory for implementors (unless otherwise specified). The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [1].

¹Infrastructure as a Service

3 OCCI JSON Rendering

The OCCI JSON Rendering specifies a rendering of OCCI instance types in the JSON data interchange format as defined in [2].

The rendering can be used to render OCCI instances independently of the protocol being used. Thus messages can be delivered by, e.g., the HTTP protocol as specified in [3].

The following media-type MUST be used for the OCCI JSON Rendering:

```
application/occi+json
```

The OCCI JSON Rendering consists of a JSON object containing information on the OCCI Core instances OCCI Kind, OCCI Mixin, OCCI Action, OCCI Link and OCCI Resource. The rendering also include a JSON object to invoke the operation identified by OCCI Actions. The rendering of each OCCI Core instance will be described in the following sections.

3.1 Entity Instance Rendering

Entity instances MUST be rendered as JSON hashmaps.

3.1.1 Resource Instance Rendering

The OCCI Resource Instance Rendering consists of a JSON object as shown in the following declaration. Appendix A.1 contains a detailed example. Table 2 defines the object members.

```
{
  "kind": String,
  "mixins": Array,
  "attributes": Object,
  "actions": Array,
  "id": String,
  "links": Array,
  "summary": String,
  "title": String,
}
```

Table 2. OCCI Resource instance rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
kind	String	immutable	1	Type identifier.
mixins	Array of Strings	mutable	0..1	List of type identifiers of associated OCCI Mixins.
attributes	Object	mutable	0..1	Instance Attributes (see 3.5.1).
actions	Array of Strings	mutable	0..1	List of type identifiers of OCCI Actions applicable to the OCCI Resource instance.
id	String	immutable	1	ID of the OCCI Resource.
links	Array of Objects	mutable	0..1	List of OCCI Links (fully rendered instances, see 3.1.2).
summary	String	mutable	0..1	Summary text of resource.
title	String	mutable	0..1	Title of resource.

3.1.1.1 Action Invocation Rendering The OCCI Action Invocation Rendering identifies an invocable operation on a OCCI Resource or OCCI Link instance. To trigger such an operation the OCCI Action Invocation Rendering is required.

The OCCI Action Invocation Rendering consists of a top-level JSON object as shown in the following declaration. Appendix A.2 contains a detailed example. Table 3 defines the object members.

```
{
  "action": String,
  "attributes": Object
}
```

Table 3. An OCCI Action invocation is rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
action	String	immutable	1	Type identifier.
attributes	Object	mutable	0..1	Instance attributes (see 3.5.1).

3.1.2 Link Instance Rendering

The OCCI Link Instance Rendering consists of a JSON object as shown in the following declaration. Appendix A.3 contains a detailed example. Table 4 defines the object members.

```
{
  "kind": String,
  "mixins": Array,
  "attributes": Object,
  "actions": Array,
  "id": String,
  "source": Object,
  "target": Object,
  "title": String
}
```

Table 4. OCCI Link instances are rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
kind	String	immutable	1	Type identifier.
mixins	Array of Strings	mutable	0..1	List of type identifiers of associated OCCI Mixins.
attributes	Object	mutable	0..1	Instance attributes (see 3.5.1).
actions	Array of Strings	mutable	0..1	List of type identifiers of OCCI Action Categories applicable to the OCCI Link instance.
id	String	immutable	1	ID of the OCCI Link.
source	Object	immutable	1	Hashmap of the link source (see 3.1.2.1).
target	Object	immutable	1	Hashmap of the link target (see 3.1.2.1).
title	String	mutable	0..1	Title of the Link

3.1.2.1 Link Instance Source/Target Rendering

The OCCI Link Instance Source/Target Rendering consists of a JSON object as shown in the following declaration. Appendix A.3 contains a detailed example. Table 5 defines the object members. `location` maps to OCCI Core's `source` and `target` model attributes and `kind` maps to OCCI Core's `target.kind` model attribute. The value of `kind` for `source` is implied by OCCI Core's model attribute value for `source`.

```
{
  "location": String,
  "kind": String
}
```

Table 5. OCCI Link sources/targets are rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
location	String	immutable	1	URI of the link target/source.
kind	String	immutable	0..1	Kind identifier, supplied if location points to an OCCI Resource.

3.2 Category Instance Rendering

Category instances MUST be rendered as JSON hashmaps.

3.2.1 Kind Instance Rendering

The OCCI Kind Instance Rendering consists of a JSON object as shown in the following declaration. Appendix A.4 contains a detailed example. Table 6 defines the top-level object members.

Table 6. OCCI Kind instances are rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
term	String	immutable	1	Unique identifier within the categorization scheme.
scheme	String	immutable	1	Categorization scheme.
title	String	immutable	0..1	Title of the OCCI Kind.
attributes	Object	immutable	0..1	Attribute description, see 9.
parent	String	immutable	0..1	OCCI Kind type identifier of the related "parent" Kind instance.
actions	Array of Strings	immutable	0..1	List of OCCI Action type identifiers.
location	String	immutable	0..1	Transport protocol specific URI bound to the OCCI Kind instance. MUST be supplied for the OCCI Kinds of all OCCI Entities except OCCI Entity itself.

```
{
  "term": String,
  "scheme": String,
  "title": String,
  "attributes": Object,
  "actions": Array,
  "parent": String,
  "location": String
}
```

3.2.2 Mixin Instance Rendering

The OCCI Mixin Instance Rendering consists of a JSON object as shown in the following declaration. Appendix A.5 contains a detailed example. Table 7 defines the top-level object members.

```
{
  "term": String,
  "scheme": String,
  "title": String,
  "attributes": Object,
  "actions": Array,
  "depends": Array,
  "applies": Array,
  "location": String
}
```

Table 7. OCCI Mixin instances are rendered with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
term	String	immutable	1	Unique identifier within the categorization scheme.
scheme	String	immutable	1	Categorization scheme.
title	String	immutable	0..1	Title of the OCCI Mixin.
attributes	Object	immutable	0..1	Attribute description, see 9.
depends	Array of Strings	immutable	0..1	List of type identifiers of the dependent Mixin instances.
applies	Array of Strings	immutable	0..1	List of OCCI Kind type identifiers this OCCI Mixin can be applied to.
actions	Array of Strings	immutable	0..1	List of OCCI Action type identifiers.
location	String	immutable	1	Transport protocol specific URI bound to the OCCI Mixin instance.

3.2.3 Action Instance Rendering

The OCCI Action Instance Rendering consists of a JSON object as shown in the following declaration. Appendix A.6 contains a detailed example. Table 8 defines the top-level object members.

Table 8. OCCI Actions are rendered inside the top-level JSON object with name *actions* as an array of JSON Objects with the following entries:

Object member	JSON type	Mutability	Multiplicity	Description
term	String	immutable	1	Unique type identifier within the categorization scheme.
scheme	String	immutable	1	Categorization scheme.
title	String	immutable	0..1	Title of the OCCI Action.
attributes	Object	immutable	0..1	Attribute description, see 9.

```
{
  "term": String,
  "scheme": String,
  "title": String,
  "attributes": Object,
}
```

3.3 Entity Collection Rendering

Collections of Entity instances MUST be rendered as JSON arrays. The content of that array is a set of entity instance renderings.

That array MUST be a member of a JSON hashmap that is associated with the relevant key name specific to the type of Entity collection being rendered.

3.3.1 Resource Collection Rendering

The JSON hashmap key-name associated with the array of resource instances MUST be *resources*.

```
{
  "resources": []
}
```

3.3.2 Link Collection Rendering

The JSON hashmap key-name associated with the array of link instances MUST be *links*.

```
{
  "links": []
}
```

3.4 Category Collection Rendering

Collections of Category instances MUST be rendered as JSON arrays. The content of that array is a set of Category instance renderings.

That array MUST be a member of a JSON hashmap that is associated with the relevant key name specific to the type of Category collection being rendered.

3.4.1 Kind Collection Rendering

The JSON hashmap key-name associated with the array of kind instances MUST be *kinds*.

```
{
  "kinds": []
}
```

3.4.2 Mixin Collection Rendering

The JSON hashmap key-name associated with the array of mixin instances MUST be *mixins*.

```
{
  "mixins": []
}
```

3.4.3 Action Collection Rendering

The JSON hashmap key-name associated with the array of action instances MUST be *actions*.

```
{
  "actions": []
}
```

Collections of Category instances are rendered as JSON arrays.

3.5 Attributes Rendering

Attribute names consist of alphanumeric characters separated by dots. The dots define a logical namespace-like hierarchy. This hierarchy is NOT reflected in JSON objects. As shown in the following declaration, the attribute name is an opaque identifier rendered as hashmap *key*. The hashmap *value* contains either a Number, a String, a Boolean, an Array or an Object (as an attribute value or an attribute description, following the Attribute Description Rendering, see 3.5.1).

```
{
  "one.two.three": Number | String | Boolean | Array | Object,
  "one.two.four"  : Number | String | Boolean | Array | Object
}
```

For examples of rendered Attributes please refer for instance to the Resource instance rendering example in Appendix A.1.

3.5.1 Attribute Description Rendering

Attribute Descriptions are rendered as JSON objects as defined in table 9

```
{
  "mutable": Boolean,
  "required": Boolean,
  "type": String,
  "pattern": Object,
  "default": String | Number | Boolean | Array | Object,
  "description": String
}
```

For examples of rendered Attribute Descriptions please refer, e.g., to the Kind rendering example in Appendix A.4.

Table 9. All properties of the Attribute definition are optional, but may contain defaults which MUST be used if the Attribute is not present in the instantiated OCCI Entity.

Object member	JSON type	Default	Description
mutable	Boolean	false	Defines if the Attribute is mutable after initialization.
required	Boolean	false	Defines if the Attribute MUST be specified at instantiation of the OCCI Entity.
type	String	string	Type of the Attribute. MUST be either "string", "number", "boolean", "array" or "object".
pattern	Object		JSON Schema [4] to validate the value of the attribute. It is recommended to specify the \$schema property for the schema used.
default	String, Number, Boolean, Array, Object	(none)	Attribute default. MUST be the same type as defined in the type property and MUST be used if the Attribute is not present in the instantiated OCCI Entity.
description	String	(none)	Description of the attribute.

4 Security Considerations

OCCI does not require that an authentication mechanism be used nor does it require that client to service communications are secured. It does RECOMMEND that an authentication mechanism be used and that where appropriate, communications are encrypted using HTTP over TLS. The authentication mechanisms that MAY be used with OCCI are those that can be used with HTTP and TLS. For further discussion see the appropriate section in [3].

5 Glossary

Term	Description
Action	An OCCI base type. Represents an invocable operation on an Entity sub-type instance or collection thereof.
Attribute	A type in the OCCI Core Model. Describes the name and properties of attributes found in Entity types.
Category	A type in the OCCI Core Model and the basis of the OCCI type identification mechanism. The parent type of Kind .
capabilities	In the context of Entity sub-types capabilities refer to the Attributes and Actions exposed by an entity instance .
Collection	A set of Entity sub-type instances all associated to a particular Kind or Mixin instance.
Entity	An OCCI base type. The parent type of Resource and Link .
entity instance	An instance of a sub-type of Entity but not an instance of the Entity type itself. The OCCI model defines two sub-types of Entity : the Resource type and the Link type. However, the term <i>entity instance</i> is defined to include any instance of a sub-type of Resource or Link as well.
Kind	A type in the OCCI Core Model. A core component of the OCCI classification system.
Link	An OCCI base type. A Link instance associates one Resource instance with another.
Mixin	A type in the OCCI Core Model. A core component of the OCCI classification system.
mix-in	An instance of the Mixin type associated with an <i>entity instance</i> . The “mix-in” concept as used by OCCI <i>only</i> applies to instances, never to Entity types.
OCCI	Open Cloud Computing Interface.
OGF	Open Grid Forum.
Resource	An OCCI base type. The parent type for all domain-specific Resource sub-types.
resource instance	See <i>entity instance</i> . This term is considered obsolete.
tag	A Mixin instance with no attributes or actions defined. Used for taxonomic organisation of entity instances.
template	A Mixin instance which if associated at instance creation-time pre-populate certain attributes.
type	One of the types defined by the OCCI Core Model. The Core Model types are Category , Attribute , Kind , Mixin , Action , Entity , Resource and Link .
concrete type/sub-type	A concrete type/sub-type is a type that can be instantiated.
URI	Uniform Resource Identifier.
URL	Uniform Resource Locator.
URN	Uniform Resource Name.

6 Contributors

We would like to thank the following people who contributed to this document:

Name	Affiliation	Contact
Michael Behrens	R2AD	behrens.cloud at r2ad.com
Mark Carlson	Toshiba	mark at carlson.net
Augusto Ciuffoletti	University of Pisa	augusto.ciuffoletti at gmail.com
Andy Edmonds	ICCLab, ZHAW	edmo at zhaw.ch
Sam Johnston	Google	samj at samj.net
Gary Mazzaferro	Independent	garymazzaferro at gmail.com
Thijs Metsch	Intel	thijs.metsch at intel.com
Ralf Nyrén	Independent	ralf at nyren.net
Alexander Papaspyrou	Adesso	alexander at papaspyrou.name
Boris Parák	CESNET	parak at cesnet.cz
Alexis Richardson	Weaveworks	alexis.richardson at gmail.com
Shlomo Swidler	Orchestratus	shlomo.swidler at orchestratus.com
Florian Feldhaus	Independent	florian.feldhaus at gmail.com
Zdeněk Šustr	CESNET	zdenek.sustr at cesnet.cz
Jean Parpaillon	Inria	jean.parpaillon at inria.fr
Philippe Merle	Inria	philippe.merle@inria.fr

Next to these individual contributions we value the contributions from the OCCI working group.

7 Intellectual Property Statement

The OGF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the OGF Secretariat.

The OGF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this recommendation. Please address the information to the OGF Executive Director.

8 Disclaimer

This document and the information contained herein is provided on an “As Is” basis and the OGF disclaims all warranties, express or implied, including but not limited to any warranty that the use of the information herein will not infringe any rights or any implied warranties of merchantability or fitness for a particular purpose.

9 Full Copyright Notice

Copyright © Open Grid Forum (2009-2016). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included as references to the derived portions on all such copies and derivative works. The published OGF document from which such works are derived, however, may not be modified in any way, such as by removing the copyright notice or references to the OGF or other organizations, except as needed for the purpose of developing new or updated OGF documents in conformance with the procedures defined in the OGF Document Process, or as required to translate it into languages other than English. OGF, with the approval of its board, may remove this restriction for inclusion of OGF document content for the purpose of producing standards in cooperation with other international standards bodies.

The limited permissions granted above are perpetual and will not be revoked by the OGF or its successors or assignees.

References

- [1] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119 (Best Current Practice), Internet Engineering Task Force, Mar. 1997. [Online]. Available: <http://www.ietf.org/rfc/rfc2119.txt>
- [2] D. Crockford, "The application/json Media Type for JavaScript Object Notation (JSON)," RFC 4627 (Informational), Internet Engineering Task Force, Jul. 2006. [Online]. Available: <http://www.ietf.org/rfc/rfc4627.txt>
- [3] R. Nyren, T. Metsch, and A. Edmonds, "Open Cloud Computing Interface – HTTP Protocol," Open Grid Forum, September 2016. [Online]. Available: <https://www.ogf.org/documents/GFD.223.pdf>
- [4] F. Galiegue, K. Zyp, and G. Court, "Json schema: core definitions and terminology," draft-zyp-json-schema-04, Internet Engineering Task Force, Jan. 2013. [Online]. Available: <http://tools.ietf.org/html/draft-zyp-json-schema-04>

A JSON Rendering Examples

A.1 Resource Instance Example

The following is an example of a rendered compute resource instance as specified in section 3.1.1.

```
{
  "kind": "http://schemas.ogf.org/occi/infrastructure#compute",
  "mixins": [
    "http://example.com/occi/infrastructure/os_tpl#debian9",
    "http://example.com/occi/infrastructure/resource_tpl#medium"
  ],
  "attributes": {
    "occi.compute.speed": 2,
    "occi.compute.memory": 4,
    "occi.compute.cores": 2,
    "com.example.occi.templates.myosmixin": {
      "mykey": "myvalue"
    }
  },
  "actions": [
    "http://schemas.ogf.org/occi/infrastructure/compute/action#start"
  ],
  "id": "urn:uuid:996ad860-2a9a-504f-8861-aeafd0b2ae29",
  "links": [
    {
      "kind": "http://schemas.ogf.org/occi/infrastructure#networkinterface",
      "mixins": [
        "http://schemas.ogf.org/occi/infrastructure/networkinterface#ipnetworkinterface"
      ],
      "attributes": {
        "occi.infrastructure.networkinterface.interface": "eth0",
        "occi.infrastructure.networkinterface.mac": "00:80:41:ae:fd:7e",
        "occi.infrastructure.networkinterface.address": "192.168.0.100",
        "occi.infrastructure.networkinterface.gateway": "192.168.0.1",
        "occi.infrastructure.networkinterface.allocation": "dynamic"
      },
      "actions": [
        "http://schemas.ogf.org/occi/infrastructure/networkinterface/action#up",
        "http://schemas.ogf.org/occi/infrastructure/networkinterface/action#down"
      ],
      "id": "urn:uuid:22fe83ae-a20f-54fc-b436-cec85c94c5e8",
      "target": {
        "location": "/network/b7d55bf4-7057-5113-85c8-141871bf7635",
        "kind": "http://schemas.ogf.org/occi/infrastructure#network"
      },
      "source": {
        "location": "/compute/996ad860-2a9a-504f-8861-aeafd0b2ae29",
        "kind": "http://schemas.ogf.org/occi/infrastructure#compute"
      }
    }
  ]
}
```

A.2 Action Invocation Example

The following is an example of a rendered stop action invocation as specified in section 3.1.1.1.

```
{
  "action": "http://schemas.ogf.org/occi/infrastructure/compute/action#stop",
  "attributes": {
    "method": "graceful"
  }
}
```

A.3 Link Instance Example

The following is an example of a rendered `networkinterface` link as specified in section 3.1.2.

```
{
  "kind": "http://schemas.ogf.org/occi/infrastructure#networkinterface",
  "mixins": [
    "http://schemas.ogf.org/occi/infrastructure/networkinterface#ipnetworkinterface"
  ],
  "attributes": {
    "occi.infrastructure.networkinterface.interface": "eth0",
    "occi.infrastructure.networkinterface.mac": "00:80:41:ae:fd:7e",
    "occi.infrastructure.networkinterface.address": "192.168.0.100",
    "occi.infrastructure.networkinterface.gateway": "192.168.0.1",
    "occi.infrastructure.networkinterface.allocation": "dynamic"
  },
  "actions": [
    "http://schemas.ogf.org/occi/infrastructure/networkinterface/action#up",
    "http://schemas.ogf.org/occi/infrastructure/networkinterface/action#down"
  ],
  "id": "urn:uuid:22fe83ae-a20f-54fc-b436-cec85c94c5e8",
  "target": {
    "location": "/network/b7d55bf4-7057-5113-85c8-141871bf7635",
    "kind": "http://schemas.ogf.org/occi/infrastructure#network"
  },
  "source": {
    "location": "/compute/996ad860-2a9a-504f-8861-aeafd0b2ae29",
    "kind": "http://schemas.ogf.org/occi/infrastructure#compute"
  }
}
```

A.4 Kind Instance Example

The following is an example of a rendered Kind instance as specified in section 3.2.1.

```
{
  "term": "compute",
  "scheme": "http://schemas.ogf.org/occi/infrastructure#",
  "title": "ComputeResource",
  "parent": "http://schemas.ogf.org/occi/core#resource",
  "attributes": {
    "occi.compute.hostname": {
      "mutable": true,
      "required": false,
      "type": "string",
      "description": "Hostname of the compute resource"
    },
    "pattern": {
      "$schema": "http://json-schema.org/draft-04/schema#",
      "type": "string",
      "pattern": "\\S+"
    }
  },
  "occi.compute.state": {
    "mutable": false,
    "required": false,
    "type": "string",
    "default": "inactive",
    "description": "State the compute resource is in"
  },
  "actions": [
    "http://schemas.ogf.org/occi/infrastructure/compute/action#start",
    "http://schemas.ogf.org/occi/infrastructure/compute/action#stop",
    "http://schemas.ogf.org/occi/infrastructure/compute/action#restart",
    "http://schemas.ogf.org/occi/infrastructure/compute/action#suspend"
  ],
  "location": "/compute/"
}
```

A.5 Mixin Instance Example

The following is an example of a rendered `medium` Resource Template Mixin as specified in section 3.2.2.

```
{
  "term": "medium",
  "scheme": "http://example.com/template/resource#",
  "depends": [
    "http://schemas.ogf.org/occi/infrastructure#resourcetpl"
  ],
  "applies": [
    "http://schemas.ogf.org/occi/infrastructure#compute"
  ],
  "attributes": {
    "occi.compute.speed": {
      "type": "number",
      "default": 2.8
    }
  },
  "title": "MediumVM",
  "location": "/template/resource/medium/"
}
```

A.6 Action Instance Example

The following is an example of a rendered `stop` Action instance as specified in section 3.2.3.

```
{
  "term": "stop",
  "scheme": "http://schemas.ogf.org/occi/infrastructure/compute/action#",
  "title": "StopComputeinstance",
  "attributes": {
    "method": {
      "mutable": true,
      "required": false,
      "type": "string",
      "default": "poweroff"
    }
  }
}
```

B OCCI JSON Schema

The JSON schema provided below validates any valid OCCI message courtesy of the `anyOf` construct below. Sub-schemas or fragments need to be used to validate specific OCCI classes.

```
{
  "id": "http://schemas.ogf.org/occi/OCCI-schema.json",
  "$schema": "http://json-schema.org/draft-04/schema#",
  "title": "OCCI v. 1.2 JSON Rendering Schema",
  "definitions": {
    "array-of-strings": {
      "type": "array",
      "items": { "type": "string" }
    },
    "kinded_uri": {
      "id": "#kinded_uri",
      "type": "object",
      "required": [ "location" ],
      "additionalProperties": false,
      "properties": {
        "location": { "type": "string" },
        "kind": { "type": "string" }
      }
    },
    "resource": {
      "id": "#resource",
      "type": "object",
      "required": [ "kind", "id" ],
      "additionalProperties": false,
      "properties": {
        "kind": { "type": "string" },
        "mixins": { "$ref": "#/definitions/array-of-strings" }
      }
    }
  }
}
```

```

      "attributes": { "$ref": "#/definitions/attributes" },
      "actions": { "$ref": "#/definitions/array_of_strings" },
      "id": { "type": "string" },
      "links": {
        "type": "array",
        "items": {
          "$ref": "#/definitions/link"
        }
      },
      "summary": { "type": "string" },
      "title": { "type": "string" }
    }
  },
  "action_invocation": {
    "id": "#action_invocation",
    "type": "object",
    "required": [ "action" ],
    "additionalProperties": false,
    "properties": {
      "action": { "type": "string" },
      "attributes": { "$ref": "#/definitions/attributes" }
    }
  },
  "link": {
    "id": "#link",
    "type": "object",
    "required": [ "kind", "id", "target", "source" ],
    "additionalProperties": false,
    "properties": {
      "kind": { "type": "string" },
      "mixins": { "$ref": "#/definitions/array_of_strings" },
      "attributes": { "$ref": "#/definitions/attributes" },
      "actions": { "$ref": "#/definitions/array_of_strings" },
      "id": { "type": "string" },
      "source": { "$ref": "#/definitions/kinded_uri" },
      "target": { "$ref": "#/definitions/kinded_uri" },
      "rel": { "type": "string" },
      "title": { "type": "string" }
    }
  },
  "kind": {
    "id": "#kind",
    "type": "object",
    "required": [ "term", "scheme" ],
    "additionalProperties": false,
    "properties": {
      "term": { "type": "string" },
      "scheme": { "type": "string" },
      "title": { "type": "string" },
      "attributes": { "$ref": "#/definitions/attribute_description" },
      "actions": { "$ref": "#/definitions/array_of_strings" },
      "parent": { "type": "string" },
      "location": { "type": "string" }
    }
  },
  "mixin": {
    "id": "#mixin",
    "type": "object",
    "required": [ "term", "scheme", "location" ],
    "additionalProperties": false,
    "properties": {
      "term": { "type": "string" },
      "scheme": { "type": "string" },
      "title": { "type": "string" },
      "attributes": { "$ref": "#/definitions/attribute_description" },
      "actions": { "$ref": "#/definitions/array_of_strings" },
      "depends": { "$ref": "#/definitions/array_of_strings" },
      "applies": { "$ref": "#/definitions/array_of_strings" },
      "location": { "type": "string" }
    }
  },
  "action": {
    "id": "#action",
    "type": "object",
    "required": [ "term", "scheme" ],
    "additionalProperties": false,
    "properties": {
      "term": { "type": "string" },
      "scheme": { "type": "string" },
      "title": { "type": "string" },
      "attributes": { "$ref": "#/definitions/attribute_description" }
    }
  },
  "resource_collection": {
    "id": "#resource_collection",
    "type": "object",
    "required": [ "resources" ],
    "additionalProperties": false,
    "properties": {
      "resources": {
        "type": "array",
        "items": {
          "$ref": "#/definitions/resource"
        }
      }
    }
  },
  "link_collection": {
    "id": "#link_collection",
    "type": "object",
    "required": [ "links" ],
    "additionalProperties": false,
    "properties": {
      "links": {

```



```

        "type": "array",
        "items": {
          "$ref": "#definitions/link"
        }
      }
    },
    "kind_collection": {
      "id": "#kind_collection",
      "type": "object",
      "required": ["kinds"],
      "additionalProperties": false,
      "properties": {
        "kinds": {
          "type": "array",
          "items": {
            "$ref": "#definitions/kind"
          }
        }
      }
    },
    "mixin_collection": {
      "id": "#mixin_collection",
      "type": "object",
      "required": ["mixins"],
      "additionalProperties": false,
      "properties": {
        "mixins": {
          "type": "array",
          "items": {
            "$ref": "#definitions/mixin"
          }
        }
      }
    },
    "action_collection": {
      "id": "#action_collection",
      "type": "object",
      "required": ["actions"],
      "additionalProperties": false,
      "properties": {
        "actions": {
          "type": "array",
          "items": {
            "$ref": "#definitions/action"
          }
        }
      }
    },
    "attributes": {
      "id": "#attributes",
      "type": "object",
      "additionalProperties": {
        "oneOf": [
          { "type": "number" },
          { "type": "boolean" },
          { "type": "string" },
          { "type": "object" },
          { "type": "array" }
        ]
      }
    },
    "attribute_description": {
      "id": "#attribute_description",
      "oneOf": [
        {
          "type": "object",
          "additionalProperties": false,
          "minProperties": 1,
          "properties": {
            "mutable": { "type": "boolean" },
            "required": { "type": "boolean" },
            "type": { "type": "string" },
            "default": {
              "oneOf": [
                { "type": "number" },
                { "type": "string" },
                { "type": "boolean" }
              ]
            },
            "description": { "type": "string" },
            "pattern": { "type": "object" }
          }
        },
        {
          "type": "object",
          "additionalProperties": false,
          "patternProperties": {
            ".+": {
              "$ref": "#/definitions/attribute_description"
            }
          }
        }
      ]
    },
    "model": {
      "id": "#model",
      "type": "object",
      "additionalProperties": false,
      "properties": {
        "resources": {
          "type": "array",
          "items": {
            "$ref": "#definitions/resource"
          }
        }
      }
    }
  }
}

```

```

    },
    "links": {
      "type": "array",
      "items": {
        "$ref": "#definitions/link"
      }
    },
    "mixins": {
      "type": "array",
      "items": {
        "$ref": "#definitions/mixin"
      }
    },
    "kinds": {
      "type": "array",
      "items": {
        "$ref": "#definitions/kind"
      }
    },
    "actions": {
      "type": "array",
      "items": {
        "$ref": "#definitions/action"
      }
    }
  }
}
},
"anyOf": [
  { "$ref": "#definitions/kind" },
  { "$ref": "#definitions/mixin" },
  { "$ref": "#definitions/action" },
  { "$ref": "#definitions/attributes" },
  { "$ref": "#definitions/attribute_description" },
  { "$ref": "#definitions/kind_collection" },
  { "$ref": "#definitions/mixin_collection" },
  { "$ref": "#definitions/action_collection" },
  { "$ref": "#definitions/resource_collection" },
  { "$ref": "#definitions/link_collection" },
  { "$ref": "#definitions/model" }
]
}

```